



PAULI BETON N.V.
Industrielaan 19
B-3730 HOESELT

Tel.: +32(0)89/41.13.00
Fax.: +32(0)89/41.67.19
Email : info@paulibeton.be

TABEL MET DE DRUKLAGEN

TYPE	WPG + WPR 13/60		WPG + WPR 16/60		
	Nuttige belasting Lengte welfsels	350 kg/m ² druklaag	650 kg/m ² druklaag	350 kg/m ² druklaag	650 kg/m ² druklaag
0.70		0 cm	0 cm	0 cm	0 cm
tot		0 cm	0 cm	0 cm	0 cm
2.50		0 cm	0 cm	0 cm	0 cm
2.60		0 cm	0 cm	0 cm	0 cm
2.70		0 cm	0 cm	0 cm	0 cm
2.80		0 cm	0 cm	0 cm	0 cm
2.90		0 cm	0 cm	0 cm	0 cm
3.00		0 cm	0 cm	0 cm	0 cm
3.10		0 cm	0 cm	0 cm	0 cm
3.20		0 cm	0 cm	0 cm	0 cm
3.30		0 cm	0 cm	0 cm	0 cm
3.40		0 cm	3 cm	0 cm	0 cm
3.50		0 cm	3 cm	0 cm	0 cm
3.60		0 cm	3 cm	0 cm	0 cm
3.70		0 cm	3 cm	0 cm	0 cm
3.80		0 cm	3 cm	0 cm	0 cm
3.90		0 cm	3 cm	0 cm	0 cm
4.00		0 cm	3 cm	0 cm	0 cm
4.10		0 cm	3 cm	0 cm	0 cm
4.20		3 cm	4 cm	0 cm	0 cm
4.30		3 cm	4 cm	0 cm	3 cm
4.40		3 cm	5 cm	0 cm	3 cm
4.50		3 cm	5 cm	0 cm	3 cm
4.60		3 cm	6 cm	0 cm	3 cm
4.70		3 cm	6 cm	0 cm	3 cm
4.80		3 cm	6 cm	0 cm	3 cm
4.90		3 cm	6 cm	0 cm	3 cm
5.00		4 cm	7 cm	0 cm	3 cm
5.10		4 cm	7 cm	3 cm	4 cm
5.20		5 cm	8 cm	3 cm	5 cm
5.30		5 cm	8 cm	3 cm	5 cm
5.40		5 cm	9 cm	3 cm	6 cm
5.50		6 cm	9 cm	3 cm	6 cm
5.60				3 cm	7 cm
5.70				3 cm	
5.80				3 cm	
5.90				3 cm	
6.00				4 cm	
6.10				4 cm	
6.20				5 cm	
6.30				5 cm	
6.40				5 cm	
6.50				5 cm	



Druklaag volgens PTV 201 probeton BENOR – doorbuiging 1/800